FEB 0 1 1982

EMERGENCY PHONE NUMBERS

During Office Hours, 8:30 A.M. - 4:30 P.M. Call (201) 499-2401 After Hours Call (201) 499-2445

GENERAL OFFICES. RAHWAY, NEW JERSEY 07065

| | | Outr (2 | 017 499-2445 | | TILLT. | 1977 | |
|---|---|--|-----------------------------|---|----------------|----------------------|--|
| CHEMICAL NAME: Ni | ckel Car | ^bonate | | | | | |
| SYNONYMS: | N/A | | | CHEMICAL FAMILY: Nickel Compounds | | | |
| FORMULA: Ni | CO ₃ | | MOLECULAR WEIGHT: 118.70 | | | | |
| TRADE NAME AND SY | 5 | M&T* Nickel | Carbonate, | Dustless | | | |
| | | | | NGREDIEI | NTS | | |
| | | MATERIAL | | | % | TLV (Units) | |
| | | Nickel | | | 27 | 0.1mg/M ³ | |
| | | | | | | | |
| e Ce.A1 | | | | | | | |
| | | and the second of the second o | | | | | |
| | | II. P | HYSICAL | DATA | | | |
| BOILING POINT, 760 mm. Hg | | | | | FREEZING POINT | | |
| SPECIFIC GRAVITY (H ₂ O = 1) | | | | VAPOR PRESSURE at 20°C. | | | |
| VAPOR DENSITY (air = 1) | | | | SOLUBILITY IN WATER, % by wt. at 20°C. | | Slight | |
| PER CENT VOLATILES BY VOLUME | | about 25 | | EVAPORATION RATE (Butyl Acetate = 1) | | , | |
| APPEARANCE AND ODOR | | Moist Green Powder Characteristic Odor | | | | | |
| l | II. FIR | RE AND E | XPLOSIC | N HAZA | RD DATA | • | |
| FLASH POINT (test method) | N/A | | AUTOIGNITION TEMPERATURE | | N/A | | |
| FLAMMABLE LIMITS IN AIR, % by volume | | LOWER | | UPPER | | | |
| EXTINGUISHING MEDIA | ⊠ Water Spray ⊠ Foam | ⊠ Carbon Dioxide ⊠ Dry Chemical | Other | | | | |
| SPECIAL FIRE FIGHTING PROCEDURES | ☑ Avoid Eye ☑ Do Not ☐ Other and Skin Breathe Contact Fumes Or dust | | | | | | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS | Dry du | st may be irm | ritating. | | | | |

| THRESHOLD LIMIT VALUE | | 0.1mg/M ³ as Nickel. | | | | | |
|---|-------------------------|--|--|--|--|--|--|
| EFFECTS OF O | VEREXPOSURE | | irritation. Avoid contact with eyes, skin and Wash thoroughly after handling. | | | | |
| EMERGENCY AND FIRST AID PROCEDURES | | EYE Flush with flowing water at least | | | | | |
| | | V. F | REACTIVITY DATA | | | | |
| STA | BILITY | | | | | | |
| UNSTABLE | STABLE | CONDITIONS TO AVOID | | | | | |
| | X | | | | | | |
| INCOMPATIBILITY (materials to avoid) | | Water Acids Bases Oxidizers Reducers Other | | | | | |
| HAZARDOUS DECOMPOSITION | N PRODUCTS | | | | | | |
| | LYMERIZATION | | | | | | |
| May Occur | Will not Occur | CONDITIONS TO AVOID | | | | | |
| | X | | | | | | |
| | ν | | OR LEAK PROCEDURES | | | | |
| ENVIRONMEN IF RELEASED CORRECTIVE A BE TAKEN | OR SPILLED | life if di Carefully container | nfined to immediate area of spill. May injure scharged to open waters. Confine area of spisweep up spilled product and transfer to a sufor disposal or recovery of nickel. | ll. itable | | | |
| WASTE DISPOS | AL METHOD | Chemically in approve | treat waste to recover nickel. Dispose of a ded dumpimg area. Follow regulations for chemical | s solid w al pollit | | | |
| | VII. S | SPECTAL | PROTECTION INFORMATION | | | | |
| RESPIRATORY PROTECTION (specify type) | | □ Not normally ☑ Other Use approved dust respirator suitable for required nickel dusts. | | | | | |
| | LOCAL EXHAUST | Recommende | | AND A | | | |
| VENTILATION | MECHANICAL (general) | Doguđeni | OTHER | | | | |
| Dubbos EYE | | Required EYE PROTECTION | □ Not normally □ Chemical □ Other necessary workers goggles | | | | |
| OTHER PROTECTIVE | | | | | | | |
| EQUIPMENT | | VIII SE | PECIAL PRECAUTIONS | <u>*************************************</u> | | | |
| PRECAUTIONA | RYLARELING | CAUTION: | May Cause Irritation. | | | | |
| PRECAUTIONARY LABELING No DOT Label required | | Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. FIRST AID: In case of contact, immediately flush eyes with plenty water for at least 15 minutes. Call a physician. Flush skin with water. Wash clothing before reuse. | | | | | |
| | OTHER PRECAUTIONS | | Launder contaminated clothing before reuse. | | | | |
| OTHER PRECA | UTIONS | Launder Co | | | | | |